

SW:Imp EWG-144 2/13/04

Patent

Amendments to the Claims:

---

1. (original): A method for controlling placement of a first part on a second part comprising,

placing a printed image containing a digital watermark on at least one of said

parts,

capturing a digital image of said printed image,

reading a grid signal contained in said digital watermark, and

determining the angular rotation of said part from said watermark grid signal.

2. (currently amended): The method of claim 1 including ~~the step of~~ reading other payload data from said watermark.

3. (currently amended): The method of claim 1 wherein said grid signal is used to determine ~~a~~ the location of said part.

4. (original): The method recited in claim 1 wherein said first part is an electronic component.

5. (original): The method recited in claim 1 wherein said second part is a printed circuit board.

SWS:Imp EWG-144 2/13/04

Patent

6. (currently amended): A system for controlling a pick and placement machine which places a first part on a second part and wherein at least one of said parts includes a printed image containing a watermark, said system comprising:

means for reading data from said digital watermark from said part, and

means for determining the orientation of said part from the data read from said watermark.

A3  
7. (currently amended): The system of claim 6 including means for reading ~~other~~ payload data from said watermark.

8. (currently amended): The system of claim 6 wherein said grid signal is used to determine a ~~the~~ location of said part.

9. (currently amended): The system of claim 6 wherein said grid signal is used to determine a ~~the~~ distance of said part from said means for reading.

10. (original): The system of claim 6 wherein said first part is an electronic component.

11. (original): The system of claim 6 wherein said second part is a printed circuit board.

SWS:Imp EWG-144 2/13/04

Patent

12. (currently amended): A robot for handling items, said robot including,  
a camera for acquiring an electronic image of a printed image containing a  
watermark,

a computer including a program ~~for from~~ reading a digital watermark in an  
electronic image acquired by said camera,

AB a controller for controlling said robot in response to ~~the~~ data acquired from said  
digital watermark.

13. (original): The robot recited in claim 12 including means for reading a grid  
signal from said digital watermark.

14. (original): The robot recited in claim 13 wherein said printed image is on an  
item to be handled by said robot.

15. (currently amended): The robot recited in claim 14 including means for  
determining a ~~the~~ distance from said camera to said item from said grid signal.

16. (currently amended): The robot recited in claim 14 including means for  
determining a ~~the~~ orientation of said item from said grid signal.

17. (new): A method for controlling placement of a first part on a second part, wherein the first part includes a digital watermark redundantly provided thereon, the digital watermark including an orientation component, said method comprising:

A4  
receiving image data corresponding to at least a portion of the first part, the portion including at least one redundant instance of the digital watermark;  
reading the orientation component of the digital watermark;  
determining an orientation of the first part through reference to at least the orientation component of the digital watermark;  
controlling placement of the first part on the second part through reference to at least the determined orientation of the first part.

18. (new): The method of claim 17, wherein the determined orientation of the first part comprises an angular rotation of the first part.

19. (new): The method of claim 17, wherein the determined orientation of the first part comprises an relative distance of the first part.

20. (new): The method of claim 17, wherein the digital watermark further comprises an identifier to identify the first part.

SWS:Imp EWG-144 2/13/04

Patent

21. (new): A robot for handling items, said robot comprising:  
an image sensor for sensing image data of an item including a digital watermark provided on a surface thereof, wherein the digital watermark comprises an orientation component;

electronic processing circuitry; and

memory including instructions stored therein for execution by the electronic processing circuitry, the instructions including instructions to:

analyze image data captured by the image sensor,

determine from analyzed image data an orientation of the item relative to the orientation component, and

provide position information based on a determined orientation of the item.

22. (new): The robot of claim 21, wherein the item includes redundant instances of the digital watermark provided on the surface.

23. (new): The robot of claim 21, wherein the position information comprises at least one of an angular rotation and relative distance.